



Part #	H × W	Aluminum
1220A	12"×20"	Aluminum Grease Filter
1616A	16"×16"	Aluminum Grease Filter
1620A	16"×20"	Aluminum Grease Filter
1625A	16"×25"	Aluminum Grease Filter
2012A	20"×12"	Aluminum Grease Filter
2016A	20"×16"	Aluminum Grease Filter
2020A	20"×20"	Aluminum Grease Filter
2025A	20"×25"	Aluminum Grease Filter
2516A	25"×16"	Aluminum Grease Filter
2520A	25"×20"	Aluminum Grease Filter
Part #	H × W	Galvanized
1220G	12"×20"	Galvanized Grease Filter
1616G	16"×16"	Galvanized Grease Filter
1620G	16"×20"	Galvanized Grease Filter
1625G	16"×25"	Galvanized Grease Filter
2012G	20"×12"	Galvanized Grease Filter
2016G	20"×16"	Galvanized Grease Filter
2020G	20"×20"	Galvanized Grease Filter
2025G	20"×25"	Galvanized Grease Filter
2516G	25"×16"	Galvanized Grease Filter
2520G	25"×20"	Galvanized Grease Filter
Part #	H × W	Stainless Steel (430)
1220SS	12"×20"	Stainless Steel Grease Filter
1616SS	16"×16"	Stainless Steel Grease Filter
1620SS	16"×20"	Stainless Steel Grease Filter
1625SS	16"×25"	Stainless Steel Grease Filter
2012SS	20"×12"	Stainless Steel Grease Filter
2016SS	20"×16"	Stainless Steel Grease Filter
2020SS	20"×20"	Stainless Steel Grease Filter
2025SS	20"×25"	Stainless Steel Grease Filter
2516SS	25"×16"	Stainless Steel Grease Filter
2520SS	25"×20"	Stainless Steel Grease Filter
10066		Filter Lock Handles
		(Sold in Pairs)

◀ GREASE FILTERS

- Continuous Grease Drain Off
- Eliminates Dripping Grease Burns
- Quick & Easy Clean-up
- Staggered Baffle Arrangement
- Reduces Fire Hazard Accidents
- Bale Handles Already Installed
- Custom Sizes Available Upon Request



GREASE SHIELD

- 20" × 30" Size Fits Most Fryers
- Constructed from 304 Stainless Steel
- NSF Approved
- Easy to Install
- De Burred for Smooth Edges
- Large Radius Corner

Part #	Description	
GS1	Grease Shield	




HOOD LIGHTS

- Cast Aluminum Base
- Tempered Glass Globe
- Pre-wired for Quick Installation

	Description
HLU HLG	Hood Light Unit Complete
HLG	Replacement Globe (coated)

▼ MULTI-PURPOSE SEALANT

- UL Listed
- 10.3 oz. Cartridge
- Temperature Range: -75°F -350°F
- 100% Silicone









Phone: 1-905-791-3102 • Fax: 1-905-791-2191 1-800-268-0146 1-800-565-3526