



FLAME TAMER

ANSUL SENTRY Dry Chemical Hand Portable Extinguishers

SENTRY dry chemical extinguishers are designed for protection of light and ordinary hazards. These compact and portable extinguishers are designed for commercial/compliance fire protection needs. All extinguishers are designed to fit most wall mounted storage cabinets.

Typical applications include: light manufacturing, warehousing, restaurants, office buildings, shop areas, auto repair shops, paint process areas, apartment buildings, parking garages, aircraft servicing areas, material handling vehicles, and many others.

Contact One of Our Dedicated Sales Representatives for More Information

SENTRY 2 ½

Model	Extinguisher Part #	Agent Capacity	UL/ULC Rating	Coast Guard Classification	Discharge Time	Maximum Effective Range	Operating Temperature Range	Agent Flow Rate	Charged Weight (with agent)	Unit Height	Unit Width	Unit Diameter
A02S / A02S VB	438946/438738	2.5lb. (1.13kg) FORAY	1-A:10-B:C	Type B,C Size I	9 Sec	11 ft (3.4m)	-65°F to 120°F (-54°C to 49°C)	0.31 lb/sec (0.14 kg/sec)	5lb. (2.27 kg)	13.75 in (349mm)	5.25 in (133 mm)	3.38583 in (8.6 cm)

SENTRY 5

Model	Extinguisher Part #	Agent Capacity	UL/ULC Rating	Coast Guard Classification	Discharge Time	Maximum Effective Range	Operating Temperature Range	Agent Flow Rate	Charged Weight (with agent)	Unit Height	Unit Width	Unit Diameter
AA05S-1 /AA05S1 VB	442260/442261	5 lb. (2.27 kg) FORAY	3-A:40-B:C	Type A, Size II Type B, C Size I	14 Sec	14 ft (4.3m)	-65°F to 120°F (-54°C to 49°C)	.036 lb/sec (0.16 kg/sec)	9 lb, 1 oz (4.12 kg)	16.75 in (425 mm)	8.5 in (216 mm)	4.44882 in (10.8 cm)
A05S/A05S VB	442238/442239	5 lb. (2.27 kg) FORAY	3-A:10-B:C	Type A, Size II Type B, C Size I	15 Sec	14 ft (4.3m)	-65°F to 120°F (-54°C to 49°C)	.037 lb/sec (0.17 kg/sec)	8 lb. 13oz (4.0kg)	16.375 in (41.6 cm)	8.5 in (216 mm)	4.44882 in (10.8 cm)
PK05S		5 lb. (2.27 kg) Purple K	60-B:C	Type B, C Size I	17 Sec	16 ft (4.9m)	-65°F to 120°F (-54°C to 49°C)	.030 lb/sec (0.14 kg/sec)	9 lb. 1 oz (4.12 kg)	16.375 in (41.6 cm)	8.5 in (216 mm)	4.44882 in (10.8 cm)

SENTRY 10

Model	Extinguisher Part #	Agent Capacity	UL/ULC Rating	Coast Guard Classification	Discharge Time	Maximum Effective Range	Operating Temperature Range	Agent Flow Rate	Charged Weight (with agent)	Unit Height	Unit Width	Unit Diameter
AA10S	436509	10 lb.(4.54 kg) FORAY	4-A:80-B:C	Type A, Size II Type B, C Size II	21 Sec	20 ft (6.1m)	-65°F to 120°F (-54°C to 49°C)	0.52 lb/sec (0.24 kg/sec)	17 lb., 0 oz (7.73 kg)	20.5 in (520 mm)	8.25 in (210 mm)	5.25 in (135mm)
PK10S	436791	10 lb.(4.54 kg) PURPLE K	80-B:C	Type B, C Size II	22 Sec	20 ft (6.1m)	-65°F to 120°F (-54°C to 49°C)	0.46 lb/sec (0.21 kg/sec)	17 lb., 14 oz (8.13 kg)	20.5 in (520 mm)	8.25 in (210 mm)	5.25 in (135mm)
C10S	436891	10 lb.(4.54 kg) PLUS-FIFTY C	60-B:C	Type B, C Size II	19 Sec	16 ft (4.9m)	-65°F to 120°F (-54°C to 49°C)	0.59 lb/sec (0.27 kg/sec)	17 lb., 14 oz (8.13 kg)	20.5 in (520 mm)	8.25 in (210 mm)	5.25 in (135mm)

SENTRY 20

Model	Extinguisher Part #	Agent Capacity	UL/ULC Rating	Coast Guard Classification	Discharge Time	Maximum Effective Range	Operating Temperature Range	Agent Flow Rate	Charged Weight (with agent)	Unit Height	Unit Width	Unit Diameter
AA20-1	434765	20 lb.(9.07 kg) FORAY	10-A:120-B:C	Type A, Size II Type B, C Size III	28 Sec	22 ft (6.7m)	-40°F to 120°F (-40°C to 49°C)	0.73 lb/sec (0.33 kg/sec)	32 lb., 2 oz (14.60 kg)	22.5 in (572 mm)	9.5 in (241 mm)	7.20472 in (183mm)
PK20	436791	20 lb.(9.07 kg) PURPLE-K	120-B:C	Type B, C Size III	30 Sec	22 ft (6.7m)	-40°F to 120°F (-40°C to 49°C)	0.67 lb/sec (0.30 kg/sec)	32 lb., 2oz (14.60kg)	22.5 in (572 mm)	9.5 in (241 mm)	7.20472 in (183mm)
C20		20 lb.(9.07kg) PLUS-FIFTY-C	80-B:C	Type B, C Size III	21 Sec	22 ft (6.7m)	-40°F to 120°F (-40°C to 49°C)	0.99 lb/sec (0.45 kg/sec)	32 lb., 2oz (14.60kg)	22.5 in (572 mm)	9.5 in (241 mm)	7.20472 in (183mm)