



Carbon Dioxide Fire Extinguisher

The Champion Pro Carbon Dioxide fire extinguisher models are extremely versatile and ready to tackle flammable liquids and electrical fire hazards.

These units are ideally suited for indoor applications where delicate equipment or processes require a clean extinguishing agent.

Carbon Dioxide is an effective and clean gaseous extinguishing agent that does not leave any residue to clean up or damage equipment.

These models are suitable for use on Class B and Class C fires.

Features

- ULC Listed
- USCG approved
- 6 year warranty
- Rechargeable
- Heavy duty chrome plated brass valve
- Stainless steel handle, lever and hose band
- Aluminum internal siphon tube
- Five year periodic hydrostatic test interval
- USCG approved - Meets D.O.T. requirements
- Easy to read piece nameplate
- DOT-3AL and TCM-3ALM specification cylinder
- Cylinders marked "Non-Shat" per Federal specifications RR-C-901E



FLAME TAMER

Speak With One of Our Dedicated Sales Representatives for More Information

[Contact Us](#)

Model Number	2B5V-2	B10V-1	B15V-1	B20V-1
Part Number	FX205 (24205)	FX208 (24208)	FX211 (24211)	FX214 (24214)
ULC Rating	5-B:C	10-B:C	10-B:C	10-B:C
Net Agent Weight (Average)	5 lb	10 lb	15 lb	20 lb
Ship Weight (Average)	15 lb	30 lb	40 lb	51 lb
Diameter	5.25 in	6.87 in	6.87 in	8 in
Height	17 in	19.3 in	26 in	26 in
Discharge Time	9 sec	10 sec	14 sec	17 sec
Discharge Range	3 - 8 ft	3 - 8 ft	3 - 8 ft	3 - 8 ft
Operating Pressure	850 psi	850 psi	850 psi	850 psi
Cylinder	Aluminum	Aluminum	Aluminum	Aluminum
Valve, Handle & Lever	Plated Brass	Plated Brass	Plated Brass	Plated Brass