



Holotron I Fire Extinguisher

Champion Pro Halotron-I fire extinguishers contain an extremely versatile and effective multi-purpose clean agent that is able to address most fire risks typically found in commercial and industrial applications.

These units are ideally suited for computer rooms, data storage, telecommunications, robotics or any high-tech industrial process that requires an effective clean agent necessitating an extended discharge range.

When experiencing delays, downtime and interruptions associated with extinguishing agent clean-up are not an option, Champion Pro Halotron-I is the choice.

Features

- ULC Listed
- USCG approved - Meets D.O.T. Requirements
- 6 year warranty
- Rechargeable
- The most effective clean agent with Class A, B and C fire capability
- Chrome plated brass valve
- Stainless steel handle and lever
- Large, easy-to-pull stainless steel pin
- Heavy-duty machined aluminum nozzles
- Steel cylinder and internal siphon tube
- 12 year hydrostatic test intervals



FLAME TAMER

Speak With One of Our Dedicated Sales Representatives for More Information

[Contact Us](#)

Model Number	2.5HB-2	5HB-2	11.5HB	15HB
Part Number	FX824 (24563)	FX826 (24567)	FX828 (23082)	FX830 (23097)
ULC Rating	2-B:C	5-B:C	1-A:10-B:C	2-A:10-B:C
Net Agent Weight (Average)	2.5 lb	5 lb	11 lb	15.5 lb
Ship Weight (Average)	6.85 lb	10.6 lb	23 lb	26.5 lb
Diameter	3 in	4.25 in	7.25 in	7.25 in
Height	14.88 in	15.25 in	16.19 in	17.13 in
Discharge Time	9 sec	9 sec	11 sec	14 sec
Discharge Range	6 - 10 ft	9 - 15 ft	9 - 15 ft	12 - 18 ft
Operating Pressure	100 psi	100 psi	125 psi	125 psi
Cylinder	Steel	Steel	Steel	Steel
Valve, Handle & Lever	Plated Brass	Plated Brass	Plated Brass	Plated Brass