

2.5 gallon Water / Loaded Stream

Fire Extinguisher

RELY

This Portable 2.5-Gallon Water Fire Extinguisher delivers industrial grade fire protection and is engineered for easy field recharging.

No Specialized Tools Required.

Special Product Features:

- Durable full stainless steel cylinder for long-lasting performance
- Heavy-duty nickel-plated brass valve with integrated wall loop and gauge guard
- Ergonomic stainless steel handle and lever with oversized stainless steel pull pin for secure operation
- Welded stainless steel syphon tube and bottom filter screen ensure reliable discharge
- Field-rechargeable design—no special tools or adapters required
- Patent-pending nozzle tip compatible with standard pneumatic quick-connect fittings for effortless pressurization



Model	P2.5WLS	Loaded Stream Charge
Part Number	FX	Accessory
ULC/UL Rating	2-A	2-A
Size	2.5 gallon	11 lbs. dry charge
Rating	2-A	2-A
Flow Rate	.36 pps	.36 pps
Operating Temp	+40°C to +48.8°C (+40°F to 120°F)	+40°C to +48.8°C (+40°F to 120°F)
Discharge Time	64.1 sec.	75.6 sec.
Discharge Range	9.14 - 12.19 m (30 - 40 ft)	9.14 - 12.19 m (30 - 40 ft) psi
Operating Pressure	850 psi	
Cylinder Valve	Stainless Steel	Stainless Steel
Body Handle & Lever	Nickel-Plated Brass	Nickel-Plated Brass
	Stainless Steel	Stainless Steel

Contact Your Rep

For more information

FLAME TAMER

Tel: (905) 791-3102

Toll Free: (800) 268-0146

Email: sales@flametamer.ca

Web: www.flametamer.ca